

INER-G s.a.r.l.
Mr. Mohamed Afif Ghaddar
Managing Partner

Laboratory Report ID : 643665
Job No. : 2011-SHRJ-001646
Client Reference : None

Sample ID : 2011-SHRJ-001646-001 **Date Taken** : Not Supplied
Product : Engine Oil **Date Submitted** : 25-May-2011
Sampling Point : Not Applicable **Date Tested** : 01-Jun-2011
Job Location : Sharjah **Drawn By** : Client
Representing : Brand Name: Iner-G, Product Name: Lubric DM 200, Product Type: Diesel Engine Oil SAE 15 W/ 40 API CH4, Batch No: 7711

Method	Test	Result	Units
ITM 2202	Clear and Bright	Pass	
ASTM D1500	ASTM Color	<4.5	
ASTM D4052	Specific Gravity @ 15°C	0.8784	
ASTM D445	Kinematic Viscosity @ 104 °F/ 40 °C	119.8	mm ² /s
ASTM D445	Kinematic Viscosity @ 212 °F/ 100 °C	15.68	mm ² /s
ASTM D2270	Viscosity Index	137	
ASTM D874	Sulfated Ash	1.92	Wt %
ASTM D92	Corrected Flash Point	224	°C
ASTM D5293	Cold Cranking Dynamic Viscosity @ -20°C	6429	mPa s
ASTM D2896	Average Base Number	17.43	mg KOH/g

Sample Received Condition : Good (No Seal)
Seal Number : None
Sampling Method : Not Applicable

The information contained herein is based on laboratory tests and observations performed by Intertek. The sample was submitted by client solely for testing. Intertek disclaims any and all liability for damage or injury which might result from the use of the information contained herein, and nothing contained herein shall constitute a guarantee, warranty or representation by Intertek with respect to the accuracy of the information, the sample, product or item described, or its suitability for use for any specific purpose.



Signed: _____

Anil Balan, Manager

Date: 01-Jun-2011