

Tempo PM 100

SAE 20W-50



High performance lubricant for gasoline and diesel engines

APPLICATIONS

All industrial vehicles

All types of services

Composition

- Developed to answer the severe technical constraints of gasoline, LPG and Diesel engines in modern passenger cars of light vans with or without turbo chargers.

- Based on high quality of mineral base oil in combination with a special additive technology.



PERFORMANCES

Meets the Specifications:

API	SL/CF
ACEA	A3/B3
MB	229.1
VW	505.00

ADVANTAGES

Increased drain intervals

- Its very high performance level insures longer drain intervals.
- Good thermal oxidation stability
- Stay in grade
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.

Very high technical performances

CHARACTERISTICS

	Units	SAE Grade 20W-50
Volumetric mass at 15°C	kg/m ³	890
Viscosity at 100°C	mm ² /s	18.00
Viscosity at 40°C	mm ² /s	159
Viscosity index	-	125
Viscosity CCS @-15°C, max	CP	9500
Flash point	°C	>201
Pour point	°C	-30
T.B.N	mgKOH/g	8.2
Sulphated Ash	% wt	0.95

The typical characteristics mentioned represents mean values.

Date Issued: 25-02-2016

INER-G S.A.L., Sidon, Lebanon
Tel: 00961 3 484870 Tel/Fax: 00961 7 260977
e-mail: info@iner-g.com
Website: www.iner-g.com

**INER-G Tempo PM100
SAE 20W-50**

 Made in
 Holland