

Tempo PM 200

SAE 10W-40



High performance lubricant for gasoline and diesel engines

APPLICATIONS

All Commercial vehicles

- Is a universal high performance fuel saving semi synthetic oil for passenger car and light vans with or without Turbo charger.



PERFORMANCES

Meets the Specifications:

OEMs approvals

API	SL/CF
ACEA	A3/B3
RN	0700
MB-Approval	229.1
VW	501.01/505.00

ADVANTAGES

Increased drain intervals

Very high technical performances

- Its very high performance level insures longer drain intervals.
- High viscosity Index.
- Very Good low temperature properties.
- Exceptional antiwear and anticorrosion properties.
- Good efficiency against bore polishing.
- Very high thermal and oxidation stability.
- Very high detergency and dispersancy levels (limits oil thickening due to soots).

CHARACTERISTICS

	Units	SAE Grade 10W-40
Volumetric mass at 15°C	kg/m ³	868
Viscosity at 100°C	mm ² /s	14.2
Viscosity at 40°C	mm ² /s	92
Viscosity index	-	158
Viscosity CCS @-15°C, max	CP	<7000
Flash point	°C	>201
Pour point	°C	- 33
T.B.N	mgKOH/g	7.9
Sulphated Ash	% wt	0.95

The typical characteristics mentioned represents mean values.

Date Issued: 25-02-2016

INER-G S.A.L., Sidon, Lebanon
Tel: 00961 3 484870 Tel/Fax: 00961 7 260977
e-mail: info@iner-g.com
Website: www.iner-g.com

**INER-G Tempo PM200
SAE 10W-40**

 Made in
 Holland