

Tempo PM 400

SAE 5W-40



High performance lubricant for gasoline and diesel engines

APPLICATIONS

All Commercial vehicles

- Is a high performance engine oil based on 100% synthetic technology for use specially in Mercedes- Benz and Porsche.

All types of services

- Adapted to meet the requirements of all gasoline and diesel engines of passenger car and light vans with or without Turbocharging.



PERFORMANCES

Meets the Specifications:

API	SN
ACEA	A3/B4
PORSCHE	A40
MB	229.5
GM-LL-A	25/B025
BMW	Longlife -01
VW	502.00/505.00
RENAULT RN	0700/0710

ADVANTAGES

Increased drain intervals

- Its very high performance level insures longer drain intervals.

Very high technical performances

- Protection to wear by cold starts
- Very high thermal oxidation stability
- Very Good low temperature properties.
- Excellent viscosity index
- Very high detergency and dispersancy levels (limits oil thickening due to soots).
- Excellent resistance against foaming, corrosion and wear.

CHARACTERISTICS

	Units	SAE Grade 5W-40
Volumetric mass at 15°C	kg/m ³	854
Viscosity at 100°C	mm ² /s	14.3
Viscosity at 40°C	mm ² /s	86
Viscosity index	-	174
Viscosity CCS @-30°C, max	CP	6600
Flash point	°C	>201
Pour point	°C	- 36
T.B.N	mgKOH/g	10.3
Sulphated Ash	% wt	1.26

The typical characteristics mentioned represents mean values.

Date Issued: 25-02-2016

INER-G S.A.L., Sidon, Lebanon
Tel: 00961 3 484870 Tel/Fax: 00961 7 260977
e-mail: info@iner-g.com
Website: www.iner-g.com

**INER-G Tempo PM300
SAE 5W-40**

 Made in
 Holland