

2 TZ



Oil for 2-stroke gasoline engines

USES

Oil for all type of two stroke gasoline engine

- such as mopeds and light-weight motorcycles (<50cc)
- used for mechanized farming (motor-mower...)

Adapted to 2 stroke motorcycle engines with independent lubricating system or premixing use.

Premix with gasoline at the percentage recommended by the manufacturer.

PERFORMANCES

Spécifications

API TC
JASO FB Level
ISO-L-EGB Level

CUSTOMER BENEFITS

Viscosity adapted to :

- 2 stroke motorcycle engines with independent lubricating system
- premixing use.

Pre-diluted and therefore suitable for separate greasing and mixing.

CHARACTERISTICS

TOTAL 2TZ	Units	
Volumetric mass at 15°C	kg/m ³	885
Viscosity at 40°C	mm ² /s	71.24
Viscosity at 100°C	mm ² /s	9.4
Viscosity index	-	112
Flash point Cleveland	°C	244
Pour point	°C	-27

The typical characteristics mentioned represent mean values.

Red colour

TOTAL LUBRIFIANTS

Le SPAZIO
562 Avenue du Parc de l'île
92029 - NANTERRE CEDEX

March 2004

1/1

2 TZ



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant