

VOLC AUTOMOTIVE ENGINE OILS





INNOVATIVE TECHNOLOGY FOR EXTREME **PERFORMANCE & PROTECTION.**

VOLC Heavy Duty Petrol & Diesel Oil

Is the ultimate formula for protection and performance that meets the changing needs of your engine. This unique multi-component technology provides:

Low wear and corrosion for long engine life

Low deposit formation to maintain engine performance

Breakdown resistance by heat for continuous protection



For more information contact
Your NER-G S.A.R.L. Dealer or Contact us on:
INER-G S.A.R.L., Sidon, Lebanon.
T: +961 7 2609770 / +961 3 484870
E: info@iner-g.com
W: www.iner-g.com

In addition to the VOLC Automotive Engine Oils Range, we also offer a complete portfolio of lubricants for every part of your Vehicle and equipment, including Diesel Engine Oils, Gear, Axle and Transmission Oils, Heavy Duty Greases, Coolants and Anti-freeze.



VOLC SAE 40 HIGH-PERFORMANCE, MINERAL ENGINE OIL

VOLC SAE 40 is a heavy-duty mono-grade petrol & diesel engine oil formulated from selected base fluids for use in passenger car and light truck engines requiring API SF/CD performance lubricants and where SAE 40 viscosity grade is acceptable.

Performance Standards

• API SF/CD

Property	Units	Typical Values
SAE Viscosity Grade	SAE	40
Density @ 15°C	kg/m ³	898
Kinematic Viscosity @ 100°C	mm ² /s	15.5
Viscosity Index	-	100
Flash Point	°C	>200
Total Base Number	mgKOH/g	8.1



It provides:

Detergent-dispersant capability keeping engine components clean


Thermal stability and oxidation resistance

Anti-wear properties

Applications

• Recommended for Petrol and Diesel engines in cars and light vans.

• Permits use at all temperature and any type of service: city, highway, mountain, rough road.



Volc Automotive Engine Oils

INNOVATIVE TECHNOLOGY
**FOR EXTREME
PERFORMANCE &
PROTECTION.**

فولك زيوت محركات السيارات
تكنولوجيا مبتكرة لأداء عالي و حماية
فائقة



من ميزاتة:

تدني التآكل لاطالة عمر المحرك

تدني تراكم الترسبات للمحافظة على أداء و نظافة المحرك

مقاومة التفكك بفعل الحرارة لحماية مستمرة للمحرك

التطبيقات:

- زيت موصى به لمحركات البنزين و الديزل في سيارات الركاب و المركبات التجارية الخفيفة.

- يمكن استخدامه تحت درجات حرارة مختلفة مثل : المدينة، الجبل، الطريق السريعة، الطرق المتعرجة.

فولك ٤٠ زيت محرك معدني عالي الأداء

هو زيت محركات البنزين و الديزل للخدمة الشاقة يتمتع بخصائص فائقة الفعالية التي تلبي الاحتياجات المتغيرة لاستخدامها في سيارات الركاب و المركبات التجارية الخفيفة التي تتطلب لزوجة ٤٠ و المطابقة لأداء API SF/CD

معايير الأداء

API SF/CD



Property	Units	Typical Values
SAE Viscosity Grade	SAE	40
Density @ 15°C	kg/m3	898
Kinematic Viscosity @ 100°C	mm2/s	15.5
Viscosity Index	-	100
Flash Point	°C	>200
Total Base Number	mgKOH/g	8.1



تكنولوجيا مبتكرة لأداء عالي و حماية فائقة

فولك زيت محركات البنزين والديزل للخدمة الشاقة يتمتع
بخصائص فائقة الفعالية للحماية والأداء التي تلبي الاحتياجات
المثيرة للمحرك. هذه التكنولوجيا الفريدة المتعددة العناصر
تساعد على:

تدني التآكل لاطالة عمر المحرك

تدني تراكم التسربات للمحافظة على أداء المحرك

مقاومة التفكك بفعل الحرارة لحماية مستمرة للمحرك



للمزيد من المعلومات الرجاء التواصل مع موظفي شركة انرجي أو التواصل مع الشركة مباشرة عبر:

شركة انرجي ش.م.م. صيدا، لبنان

تلفون : +٩٦١٧٢٦٠٩٧٧ ، +٩٦١٣٤٨٤٨٧

البريد الالكتروني: info@iner-g.com

الموقع الالكتروني : www.iner-g.com

بالإضافة الى مجموعة زيوت المحركات فولك، تقدم شركة انرجي مجموعة كاملة من الزيوت التي تلبي احتياجات السيارات،
الشاحنات، المعدات بما في ذلك زيوت محركات الديزل، زيوت الفيتاس، الشحوم الثقيلة و مياه مكافحة الجليد

فولك زيوت محركات السيارات للخدمة الشاقة

